


DETAIL A
SCALE 3:1



NOTES: (UNLESS OTHERWISE SPECIFIED)

RATING: TO BE MARKED ON HOUSING

16A, 125VAC cULus

10A, 250VAC cULus

UL ENDURANCE RATING: 6000 CYCLES

INITIAL CONTACT RESISTANCE: 50m Ω (MAX)

INSULATION RESISTANCE: 500 VDC 100M Ω (MIN)

DIELECTRIC STRENGTH: 1500 VAC FOR 1 MINUTE.

OPERATION TEMPERATURE: -25°C TO +85°C

WATERPROOF: IP65 CAPABLE




ACTUATOR: BLACK, PC (94-V2)

TERMINALS: .031 $\pm$.001[0,8 $\pm$ 0,03] X .189 $\pm$.004[4,8 $\pm$ 0,1]




HOLE $\varnothing$.055 $\pm$.008[1,4 $\pm$ 0,2]

HOUSING: BLACK, NYLON 66 (94-V2).

WATERPROOF RUBBER: BLACK, SILICONE.




SCALE 3:2



MOUNTING HOLES	
FIG.	PANEL THICKNESS
1	.059 TO .098 [1.5 TO 2.5]
2	.028 TO .098 [0.7 TO 2.5]

DWN: C RAMOS
APVD: J RUMMELHART
DATE: 17-Jun-08

THIRD ANGLE PROJECTION



PROJECT/ CSR
N/A

CONFIDENTIAL AND PROPRIETARY:
ALL INFORMATION OR INVENTIONS CONTAINED IN THIS DOCUMENT OR DERIVED FROM THE INFORMATION THEREIN IS OWNED BY ZF ELECTRONIC SYSTEMS, AND IS CONFIDENTIAL AND PROPRIETARY. REVIEW OR POSSESSION OF THIS DOCUMENT INDICATES AGREEMENT THAT SUCH INFORMATION AND INVENTIONS WILL NOT BE DISCLOSED, REPRODUCED OR OTHERWISE USED IN ANY WAY WITHOUT EXPRESS WRITTEN PERMISSION FROM AN AUTHORIZED REPRESENTATIVE OF ZF ELECTRONIC SYSTEMS.

TOLERANCE UNLESS SPECIFIED

DWG UNITS	X.XX	X.XXX	ANGLES
INCHES	$\pm$ 0.02	$\pm$ 0.012	$\pm$ 5.0 °



ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.

NAME / DESCRIPTION

KD-DPDT ON-OFF-ON NON-LIGHTED

ITEM NO. KDH3CNA1BBB

SCALE: 1:1 SH 1 OF 1

G	Z000432191	14-Nov-17	JPD	ELL
REV	ECO NO.	DATE	PREP	APVD