

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. RATING TO BE MARKED ON ROCKER:

cRL **US** 10A 125VAC
8A 250VAC
1/4HP 125/250VAC

(B) **cRL** **US** 10(4)A 250V~T125/55 10E3

cRL **US** 12(4)A 125/250V~

cRL **US** 16RA 6~30VDC.



2. INITIAL CONTACT RESISTANCE: 20mΩ (MAX.)

3. INSULATION RESISTANCE: 100MΩ MIN. AT 500VDC.

4. DIELECTRIC STRENGTH: 1500VAC FOR 1 MINUTE.

5. ILLUMINATED LED 12VDC (NO NEED TO DISTINGUISH BETWEEN THE ANODE AND AND CATHODE POLARITY.)

B	Z000689143	5-9-2023	TCH	ELL	PROJECT/ CSR	DWG UNITS	X.XX	X.XXX	ANGLES	C	ITEM NO. RRA22H3BBRHN
REV	ECO NO.	DATE	PREP	APVD	N/A	INCHES	± 0.02	± 0.012	± 5.0 °	SCALE:	N/A SH 1 OF 1

DWN: JPD		 ZF Electronic Systems				PLEASANT PRAIRIE, WISCONSIN U.S.A.			
APVD: ELL						NAME / DESCRIPTION RR SERIES - SINGLE POLE, QC, LIGHTED			
DATE: 19-Jan-18									
THIRD ANGLE PROJECTION									
L	PROJECT/ CSR	DWG UNITS	X.XX	X.XXX	ANGLES	C	ITEM NO. RRA22H3BBRHN		
	N/A	INCHES	± 0.02	± 0.012	± 5.0 °	SCALE:		N/A	SH 1 OF 1