Switch Product Overview

DH WG DG DJ/SJ DK/SK DR DB DC DZ D4/W4 E GP E/F6 E/F7 F8

Series Name	Size in mm	Switch Type	max. Electrical Rating	UL Approved	ENEC Approved	Mounting: Threaded Ferrule	Mounting: Holes	Mounting: Snap In	Mounting: Posts (optional)	Degree of Protection	Max. Operating Temp °C	Circuitry: SPDT	Circuitry: DPDT	Circuitry: SPST	Circuitry: Contact gap > 3 mm	Terminals: Quick Connect	Terminals: PCB	Terminals: Solder	Terminals: Screw	Terminals: Wire Leads	Actuator Types: Button	Actuator Types: Flat Lever	Actuator Types: Simulated Roller	Actuator Types: Roller	Contact System: Wiping / Sliding	Contact System: Positive Break Action	Contact System: Snap Action	Contact System: Push Button
DH	8.4 x 2.7 x 6.55	Ultraminiature	500 mA, 30 VDC				•			IP40	85	•					•	•			•		•				•	
WG	8.3 x 6.5 x 5.3	Subsubminiature	100 mA, 12 VDC						•	IP67	85			•			•	•			•	•	•		•			
DG	12.8 x 5.8 x 6.6	Subsubminiature	3 A, 250 VAC 3 A , 30 VDC		•		•		•	IP40	125	•					•				•	•		•			•	
DJ	15.2 x 8.15 x 6.4	Subsubminiature	2 A, 12 VDC						•	IP67	85	•		•			•	•		•	•						•	
SJ	15.2 x 6.4 x 8.1	Subsubminiature	100 mA, 12 VDC						•	IP67	85			•			•	•		•	•				•			
DK	14.7 x 6.8 x 5.4	Subsubminiature	2 A, 12 VDC						•	IP65*	85	•		•			•	•		•	•	•	•				•	
SK	14.7 x 5.4 x 6.8	Subsubminiature	100 mA, 12 VDC						•	IP65*	85			•			•	•		•	•	•	•		•			
DR	13.7 x 6.8 x 5.4	Subsubminiature	2 A, 12 VDC						•	IP40	85	•					•	•			•						•	
DB	20.0 x 9.65 x 6.5	Subminiature	100 mA / 10 A, 250 VAC	•	•		•		•	IP50	120	•		•		•	•	•			•	•	•	•			•	
DC	20.0 x 10.05 x 6.5	Subminiature	100 mA / 10 A, 250 VAC	•	•		•		•	IP67	120	•		•		•	•	•		•	•	•	•	•			•	
DZ	20.0 x 9.7 x 6.5	Subminiature	3 A, 250 VAC	•	•		•			IP40	85			•		•					•					•	•	
DCJK	20.0 x 10.2 x 6.4	Subminiature	100 mA / 10 A, 250 VAC				•		•	IP67	120	•		•			•	•		•	•	•	•	•			•	
D4	27.8 x 15.9 x 10.3	Miniature	100 mA / 21 A 250 VAC	•	•		•			IP40	150	•		•		•	•	•			•	•	•	•			•	
W4	27.8 x 15.9 x 10.3	Miniature	100 mA / 16 A 250 VAC	•	•		•			IP40	85	•		•		•					•	•	•	•	•		•	
E	46 x 28,6 x 16,4	General Purpose	25 A, 250 VAC	•		•	•			IP40	150	•	•	•		•					•	•		•			•	
GP	49.6 x 17.6 x 23.7	General Purpose	25 A, 250 VAC	•	•	•	•			IP40	40	•						•	•		•	•		•			•	
E/F6	25.6 x 26.6 x 13.72	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•		•					•							•
E/F7	31.5 x 26.6 x 13.72	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•		•					•							•
F8	31.5 x 37.5 x 13.3	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•	•	•					•					•		•

Specifications are subject to change without notice. If you require PFAS free products, please contact the factory.
*IP67 available on request.
Please look for additional technical information on the website.
Version 4.0 – January 2026.

ZF Friedrichshafen AG · Graf-Zeppelin-Straße 1 · 91275 Auerbach
switches-sensors@zf.com · https://switches-sensors.zf.com