



GENERAL CHARACTERISTICS

Operating Force	Max. 90gf
Release Force	Min. 10gf
Contact Resistance	Max. 50mΩ
Insulation Resistance	Min. 100mΩ 500VDC
Dielectric Voltage	500VAC 60 Sec.
Mechanical Life	50,000 Cycles
Electrical Life	30,000 Cycles
Rating	5-500mA 30VDC
Operating Temperature	-25 to 85°C

NO.	PARTS	MATERIALS
01	COVER	PA
02	BASE	PPA
03	ACTUATOR	PBT
04	CONTACT	Au ALLOY
05	MOVING BLADE	COPPER BERYLLIUM
06	TERMINAL (COM)	SILVER PLATE BRASS
07	TERMINAL (NO)	SILVER PLATE BRASS
08	TERMINAL (NC)	SILVER PLATE BRASS
09		



采埃孚电子(珠海)有限公司
ZF Electronics (Zhuhai) Company Limited

图号	变更内容	修改	核准	日期	批准	日期	制图	日期	设计	日期	审核	日期	材料	单位	比例	角法	张数	工程图	版本	图号
MARK.	DEFINITION	REVISE	APPROVE	DATE	APPROVE	DATE	DRAW	DATE	DESIGN	DATE	CHECKED	DATE	MATERIAL	UNIT	SCALE	PROJ.	SHEET	ENG. DWG	REV.	DWG NO.
③							H,QIN	2020.12.11	H,QIN	2020.12.11	J.WANG	2020.12.16		mm	1:1	⊕	第1页,共1页			DHGC-C5AA
②							H,QIN	2020.12.11	H,QIN	2020.12.11	J.WANG	2020.12.16		mm	1:1	⊕	第1页,共1页			DHGC-C5AA
①							J.WANG	2020.12.16	J.WANG	2020.12.16	J.WANG	2020.12.16		mm	1:1	⊕	第1页,共1页			DHGC-C5AA

系列: DH 微动开关/SUBMINIATURE SWITCH
料号: DHGC-C5AA
图号: DHGC-C5AA

比例: 1:1
角法: ⊕
张数: 第1页,共1页
工程图: ENG. DWG
版本: REV.
图号: A0