

Sensor Product Overview



Series Name	Technology					Mounting					Sensor Function							Connection			Magnets	
	Hall Effect	Reed	Unipolar Switch	Latching		Threaded	Snap In	Mounting Holes	Flange Mount		Magnetic proximity	Speed	Dual Speed	Speed & Direction	Vane	Angular Rotation	Linear Position	Max. Operating Temp °C	Integral Connector	Pins	Wires	Compatible Accessories
MP1013	•		•	•			•			•								150			•	
MP1014	•		•	•				•		•								85			•	
MP1007	•		•			•				•								150			•	
MP1021	•		•	•				•		•								85			•	
MP2007		•				•				•								105			•	AS101001
MP2017		•								•								105			•	AS201701
MP2018		•						•		•								105			•	AS201801
MP2019		•						•		•								105			•	AS201901
VN1015	•							•						•				85		•	•	
GS1001	•					•						•						125	•		•	
GS1002	•					•						•						125	•		•	
GS1005	•					•						•						125	•		•	
GS1007	•					•						•						125			•	
GS1012	•							•				•						125	•		•	
GS101205	•							•				•						140	•		•	
GS102301	•					•						•						140	•		•	
GS82	•							•				•						85	•		•	
LIN	•							•								•		140			•	
SD101201	•							•					•					125	•		•	
SD501201	•							•				•						125	•		•	
SD74	•							•					•					140			•	
AN1	•							•							•			125	•		•	
AN8	•							•							•			125	•		•	AS500106 / 709-21955
AN9	•							•							•			125			•	AS500106 / 709-21955
ANG	•							•							•			140			•	AS500106 / 709-21955

Specifications are subject to change without notice
 Please look for additional technical information on the website
 Version 1.0 - March 2023

ZF Friedrichshafen AG · Graf-Zeppelin-Straße 1 · 91275 Auerbach ·
 switches-sensors@zf.com · www.switches-sensors.zf.com

