

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. ELECTRICAL RATING:

c **ZF** us 20A 125 VAC, 12A 250 VAC.

c **ZF** us **16(8)A** 125/250V~ T55.

2. OPERATING FORCE: 500 GRAMS± 200 GRAMS.

3. DIELECTRIC VOLTAGE - WITHSTAND: 1,000 VAC FOR 1 MINUTE.
INSULATION RESISTANCE: DC 500V 100MΩ (MIN.).
CONTACT RESISTANCE: 20mΩ INITIAL (MAX.).


4. HOUSING AND ROCKER COLOR: BLACK
NO LEGEND.

5. TERMINALS (3): .187±.004/- .002 [4,7±0,1/-0,05] WIDE
X .031±.001 [0,8±0,03] THICK, HOLE DIAMETER .063 [1,6]

6. RECOGNIZED TO U.S. AND CANADIAN REQUIREMENTS UNDER
THE COMPONENT RECOGNITION PROGRAM OF
UNDERWITERS LABORATORIES, INC.

DWN: TLM
APVD: ELL
DATE: 26-Jun-07

THIRD ANGLE PROJECTION



PROJECT/ CSR
N/A

CONFIDENTIAL AND PROPRIETARY:
ALL INFORMATION OR INVENTIONS CONTAINED IN THIS
DOCUMENT OR DERIVED FROM THE INFORMATION THERE
IN IS OWNED BY ZF ELECTRONIC SYSTEMS, AND IS
CONFIDENTIAL AND PROPRIETARY. REVIEW OR
POSSESSION OF THIS DOCUMENT INDICATES AGREEMENT
THAT SUCH INFORMATION AND INVENTIONS WILL NOT BE
DISCLOSED, REPRODUCED OR OTHERWISE USED IN ANY
WAY WITHOUT EXPRESS WRITTEN PERMISSION FROM AN
AUTHORIZED REPRESENTATIVE OF ZF ELECTRONIC
SYSTEMS.

TOLERANCE UNLESS SPECIFIED

DWG UNITS	X.XX	X.XXX	ANGLES
INCHES	± 0.02	± 0.012	± 5.0 °



ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.

NAME / DESCRIPTION

SPEC. DRAWING

B ITEM NO. SRJ23A3BBBNN

SCALE: 3.000 SH 1 OF 1

G	Z000453247	17-Apr-18	JPD	ELL
REV	ECO NO.	DATE	PREP	APVD

ORIGINAL ON PRO/E