



NOTES (UNLESS OTHERWISE SPECIFIED):

1. RECOMMENDED MOUNTING: #6-32 FASTENER WITH 6.00 IN-LB (7.00 KGF-CM) OF TORQUE MAXIMUM.
2. RECOGNIZED TO U.S. AND CANADIAN REQUIREMENTS UNDER THE COMPONENT RECOGNITION PROGRAM OF UNDERWRITERS LABORATORIES, INC.
3. ALL CHARACTERISTICS ARE TAKEN AT THE ACTUATION LINE AND MEASURED FROM THE REFERENCE LINE.
4. FOR MARKING AND NAMING SPECIFICATION SEE ES021295.

CHARACTERISTICS	
ELECTRICAL RATING	15A 250VAC (cULus) T55°C 15A 250V~ (VDE)-5T40
TERMINAL	SCREW
OPER. FORCE MAX.	349 GMS
RELEASE FORCE MIN.	114 GMS
PRETRAVEL MAX.	.016 [0.41 mm]
OVERTRAVEL MIN.	.217 [5.51 mm]
MOVE. DIFF. MAX.	.002 [0.05 mm]
OPERATING POSITION	.826 TO .890 [20.98 TO 22.60 mm]

DWN: TLM/JED		CONFIDENTIAL AND PROPRIETARY: ALL INFORMATION OR INVENTIONS CONTAINED IN THIS DOCUMENT OR DERIVED FROM THE INFORMATION THERE IN IS OWNED BY ZF ELECTRONIC SYSTEMS, AND IS CONFIDENTIAL AND PROPRIETARY. REVIEW OR POSSESSION OF THIS DOCUMENT INDICATES AGREEMENT THAT SUCH INFORMATION AND INVENTIONS WILL NOT BE DISCLOSED, REPRODUCED OR OTHERWISE USED IN ANY WAY WITHOUT EXPRESS WRITTEN PERMISSION FROM AN AUTHORIZED REPRESENTATIVE OF ZF ELECTRONIC SYSTEMS.				<div></div> <div>ZF Electronic Systems</div> <div>PLEASANT PRAIRIE, WISCONSIN U.S.A.</div> <div>NAME / DESCRIPTION</div>			
APVD: SG									
DATE: 21-JUL-04									
THIRD ANGLE PROJECTION		<div></div>				SPEC DRAWING			
		TOLERANCE UNLESS SPECIFIED				C	ITEM NO. GPTCNH11		
PROJECT/ CSR		DWG UNITS	X.XX	X.XXX	ANGLES				
VD	4000000138	INCH	± 0.02	± 0.015	± 5 °	SCALE: NOT TO SCALE		SH 1 OF 1	

ORIGINAL ON PROJE