

# WATERPROOF ROCKERS



Series Name	Panel Cut-Out Approx Inches (mm)	Max UL Current Rating	V DC Max UL Current Rating	Style		Approvals				Circuitry				Switch Function						Terminals				Actuator													
				Rocker	Pushbutton	UL	CSA	cULus	VDE	Rating	Lighted - neon	Lighted - LED	SPST	SPDT	DPST	DPDT	On-Off	On-On	(On)-Off	On-(Off)	On-(On)	On-Off-On	On-Off-(On)	(On)-Off-(On)	0.187" QC	0.250" QC	PCB Straight	Solder	Screw	Flat	Curved	2-Color LED					
KC	Ø 0.795 (20.2)	10 A 250 V AC 16 A 125 V AC	▪	▪		▪	▪		IP65	▪	▪			▪										▪		▪	▪										
KD	Ø 0.795 (20.2)	10 A 250 V AC 16 A 125 V AC	▪	▪			▪		IP65	▪	▪			▪	▪									▪													
KF	Ø 0.795 (20.2)	6 A 250 V AC 10 A 125 V AC	▪	▪			▪		IP65	▪	▪			▪		▪								▪													
KG	1.441 x 0.835 (36.0 x 21.2)	10 A 250 V AC 20 A 125 V AC	▪	▪			▪		IP56					▪	▪	▪	▪	▪	▪	▪	▪	▪	▪			▪		▪									
KM	1.441 x 0.835 (36.0 x 21.2)	10 A 250 V AC 20 A 125 V AC	▪	▪					IP56		▪			▪	▪	▪	▪	▪	▪	▪	▪	▪	▪			▪											
KR	0.764 x 0.512 (19.4 x 13.0)	10 A 250 V AC 16 A 125 V AC	▪	▪			▪		IP65	▪	▪			▪	▪									▪													
KS	1.441 x 0.835 (36.0 x 21.2)	10 A 277 V AC 16 A 125 V AC	▪	▪			▪		IP56					▪	▪											▪		▪									
KT	1.454 x 0.602 (36.8 x 15.2)	10 A 250 V AC 20 A 125 V AC	▪	▪			▪	▪	IP56		▪			▪	▪											▪											

