

# CHERRY WATERPROOF ROCKERS



KC/KD



KF



KG



KM



KR



KS



KT

Series Name	Panel Cut-Out Approx Inches (mm)	Max UL Current Rating	Style		Approvals		Circuitry				Switch Function						Terminals			Actuator											
			Rocker	Pushbutton	UL	CSA	eULus	VDE	IP Rating	Lighted - Neon	Lighted - LED	SPST	SPDT	DPST	DPDT	On-Off	On-On	(On)-Off	On - (Off)	On - (On)	On-Off-On	On - Off - (On)	(On) - Off - (On)	0.187" QC	0.250" QC	PCB Straight	Solder	Screw	Flat	Curved	2-Color LED
KC	Ø0.795 (20.2)	16A 125VAC	■				■	■		IP56	■	■	■											■		■	■		■		
KD	Ø0.795 (20.2)	16A 125VAC	■				■			IP56	■	■			■	■								■					■		
KF	Ø0.795 (20.2)	10A 125VAC		■			■			IP65	■	■	■											■					■		
KG	1.441 x 0.835 (36.0 x 21.2)	20A 125VAC	■				■			IP56		■	■	■	■	■	■	■	■	■	■	■		■		■	■			■	
KM	1.441 x 0.835 (36.0 x 21.2)	20A 125VAC	■							IP56		■	■	■	■	■	■	■	■	■	■	■		■					■	■	
KR	0.764 x 0.512) (19.4 x 13.0)	16A 125VAC	■				■			IP65	■	■	■	■				■	■	■				■					■		
KS	1.441 x 0.835 (36.0 x 21.2)	16A 125VAC	■				■			IP56		■	■					■	■					■		■	■		■		
KT	1.454 x 0.602 (36.8 x 15.2)	20A 125VAC	■				■	■		IP56		■	■	■				■	■					■					■		