

CHERRY SNAP SWITCHES



DH



DG



DB



DC



E5x



E7x



D4



E Min



E General Purpose



GP



E Panel Mount



F80

Series Name	Switch Type (Size)	Max. UL Current Rating	UL Approved	VDE Approved	Mounting				Degree of Protection	Max. Temp °C	Circuitry				Terminals				Actuator Types						
					Threaded Ferrule	Mounting Holes	Snap In				SPDT	DPDT	SPST	Line Interrupt	Quick Connect	PC	Solder	Screw	Wire Leads	Button	Flat Lever	Simulated Roller	Roller	Wire Form	
DH	Ultraminiature	500mA 30 VDC							70																
DG	Subsubminiature	3A 125 VAC	■						85	■															
DJ	Subsubminiature	2A 12 VDC						IP67	85	■															
DK	Subsubminiature	2A 12 VDC						IP65	85	■															
DR	Subsubminiature	2A 12 VDC							85	■															
DB	Subminiature	10.1A 125/250 VAC	■	■				IP40	120	■		■		■	■										
DC	Subminiature	10.1A 125/250 VAC	■	■				IP67	120	■		■		■	■		■								
DZ	Subminiature	3A 125/250 VAC	■	■					85	■		■		■	■										
DCJK	Subminiature	3A 12 VDC						IP67	120	■		■		■	■		■								
E5x	Miniature	6A 250 VAC	■						85	■		■		■											■
E7x	Miniature	10.1A 125/250 VAC	■						85	■		■					■								■
D3	Miniature	16A 125/250 VAC	■	■					85	■		■		■	■	■	■								
D4	Miniature	21A 125/250 VAC	■	■				IP40	150	■		■		■	■	■	■								
E miniature	Miniature	25A 125/250 VAC	■						150	■		■		■	■	■									
E General Purpose	General Purpose	30.1A 125/250 VAC	■						150	■	■	■		■											
GP	General Purpose	20A 125/250 VAC	■						85	■		■			■	■									
E Panel Mount	Panel Mount	16A 125/250 VAC	■	■					85	■	■	■		■											
F80	Panel Mount	16A 125/250 VAC	■	■					85				■	■											