

NOTES: (UNLESS OTHERWISE SPECIFIED):

RATING TO BE MARKED ON ROCKERS:  
16A,125/250 VAC 1/4HP  
16A,250VAC 1/4HP  
3/4HP 250 VAC.

16(4)A, 250VAC T125/55 10E3


16(4)A 125/250V~

ILLUMINATED: 220 VAC COLOR: GREEN.

DIELECTRIC WITHSTAND VOLTAGE: 1000VAC FOR 1 MINUTE.  
INSULATION RESISTANCE:100M  $\Omega$  MIN. AT 500 VDC  
INITIAL CONTACT RESISTANCE:20m  $\Omega$  MAX.

TERMINALS: .031 $\pm$ .002[0.8 $\pm$ 0.03]X.248+.004/- .002[6.3+0.1/-0.05]  
HOLE  $\varnothing$ .067 $\pm$ .004[1.7 $\pm$ 0.1]

SWITCHING CIRCUIT



MARKING

MOUNTING HOLE

RECOMMENDED PANEL THICKNESS  
.030 TO .049

SCALE 1:1

A		2025-06-25	ELL	ELL
REV	ECO NO.	DATE	PREP	APVD

DWN: ELL
APVD: ELL
DATE: 25-JUN-25
THIRD ANGLE PROJECTION
PROJECT/ CSR
N/A

CONFIDENTIAL AND PROPRIETARY:  
ALL INFORMATION OR INVENTIONS CONTAINED IN THIS  
DOCUMENT OR DERIVED FROM THE INFORMATION THERE  
IN IS OWNED BY ZF ELECTRONIC SYSTEMS, AND IS  
CONFIDENTIAL AND PROPRIETARY. REVIEW OR  
POSSESSION OF THIS DOCUMENT INDICATES AGREEMENT  
THAT SUCH INFORMATION AND INVENTIONS WILL NOT BE  
DISCLOSED, REPRODUCED OR OTHERWISE USED IN ANY  
WAY WITHOUT EXPRESS WRITTEN PERMISSION FROM AN  
AUTHORIZED REPRESENTATIVE OF ZF ELECTRONIC  
SYSTEMS.

TOLERANCE UNLESS SPECIFIED			
DWG UNITS	X.XX	X.XXX	ANGLES
INCH	$\pm$ 0.02	$\pm$ 0.012	$\pm$ 5.0 °



ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.

NAME / DESCRIPTION

SPECIFICATION DRAWING

ITEM NO. WRG32F2BBREN

SCALE: 2:1 SH 1 OF 1