



SCALE 1:1

NOTES (UNLESS OTHERWISE SPECIFIED):

1. ELECTRICAL CHARACTERISTICS:

RATING TO BE MARKED ON HOUSING:



10A 125 VAC
8A 250 VAC
1/4 HP 125/250VAC

B 10(4)A 250V~ T125/55

12(4)A 125/250V~

DIELECTRIC WITHSTAND VOLTAGE: 1500 VAC FOR 1 MINUTE
INSULATION RESISTANCE: 100MΩ MIN. AT 500 VDC
INITIAL CONTACT RESISTANCE: 20mΩ MAX.
ELECTRICAL LIFE: 10,000 CYCLES


2. TERMINAL (4): SOLDER TAG .185+.004/- .002 [4,7+0,1/-0,05] WIDE
X .031±.001 [0,8±0,03] THK.
HOLE DIAMETER .091 [2.3].



B



MARKING



PANEL THICKNESS	DIM. X	DIM. Y
.030 TO .049 [0.75 TO 1.25]	.756 ^{+.004} _{-.000} [19.2 ^{+0.1} ₋₀]	.508 ^{+.006} _{-.000} [12.9 ^{+0.15} ₋₀]
.049 TO .079 [1.25 TO 2]	.764 ^{+.004} _{-.000} [19.4 ^{+0.1} ₋₀]	
.079 TO .118 [2 TO 3]	.780 ^{+.004} _{-.000} [19.8 ^{+0.1} ₋₀]	

DWN: JPD

APVD: ELL

DATE: 05-Dec-17

THIRD ANGLE PROJECTION

PROJECT/ CSR

N/A

TOLERANCE UNLESS SPECIFIED

DWG UNITS	X.XX	X.XXX	ANGLES
INCHES	± 0.02	± 0.012	± 5.0 °

ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.

NAME / DESCRIPTION

SPECIFICATION DRAWING

B ITEM NO. LRA32H2FBBNN

SCALE: 3:1 SH 1 OF 1

B	Z000686755	2023-04-25	TCH	ELL
REV	ECO NO.	DATE	PREP	APVD