

NOTES: (UNLESS OTHERWISE SPECIFIED):

RATING TO BE MARKED ON ROCKERS:
16A, 125/250 VAC 1/4HP
16A, 250VAC 1/4HP
3/4HP 250 VAC.

16(4)A, 250VAC T125/55 10E3


16(4)A 125/250V~

ILLUMINATED: 220 VAC COLOR: GREEN.

DIELECTRIC WITHSTAND VOLTAGE: 1000VAC FOR 1 MINUTE.
INSULATION RESISTANCE: 100M Ω MIN. AT 500 VDC
INITIAL CONTACT RESISTANCE: 20m Ω MAX.

TERMINALS: .031 $\pm$.002[0.8 $\pm$ 0.03]X.248+.004/- .002[6.3+0.1/-0.05]
HOLE $\varnothing$.067 $\pm$.004[1.7 $\pm$ 0.1]

SWITCHING CIRCUIT



MARKING

MOUNTING HOLE

RECOMMENDED PANEL THICKNESS
.030 TO .049

SCALE 1:1



ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.


NAME / DESCRIPTION

SPECIFICATION DRAWING

ITEM NO. WRG32F2BBGEN

SCALE: 2:1 SH 1 OF 1

DWN: TLM
APVD: ELL
DATE: 11-OCT-12
THIRD ANGLE PROJECTION



PROJECT/ CSR
4000000138

TOLERANCE UNLESS SPECIFIED

DWG UNITS	X.XX	X.XXX	ANGLES
INCH	$\pm$ 0.02	$\pm$ 0.012	$\pm$ 5.0 °

C	Z000724324	2024-02-29	TCH	ELL
REV	ECO NO.	DATE	PREP	APVD