

NOTES: (UNLESS OTHERWISE SPECIFIED):

RATING TO BE MARKED ON ROCKERS:
16A, 125/250 VAC 1/4HP
16A, 250VAC 1/4HP
3/4HP 250 VAC.

16(4)A, 250VAC T125/55 10E3


16(4)A 125/250V~

ILLUMINATED: 220 VAC COLOR: GREEN.

DIELECTRIC WITHSTAND VOLTAGE: 1000VAC FOR 1 MINUTE.
INSULATION RESISTANCE: 100M Ω MIN. AT 500 VDC
INITIAL CONTACT RESISTANCE: 20m Ω MAX.

TERMINALS: $.031 \pm .002 [0.8 \pm 0.03] \times .248 + .004 / -.002 [6.3 + 0.1 / -0.05]$
HOLE $\varnothing .067 \pm .004 [1.7 \pm 0.1]$

SWITCHING CIRCUIT




MARKING

MOUNTING HOLE

RECOMMENDED PANEL THICKNESS
.030 TO .049

SCALE 1:1

DWN: ELL
APVD: ELL
DATE: 25-JUN-25
THIRD ANGLE PROJECTION



PROJECT/ CSR
N/A



ZF Electronic Systems

PLEASANT PRAIRIE, WISCONSIN U.S.A.
NAME / DESCRIPTION

SPECIFICATION DRAWING

ITEM NO. WRG32F2BBREN

SCALE: 2:1 SH 1 OF 1

A		2025-06-25	ELL	ELL
REV	ECO NO.	DATE	PREP	APVD