

Rockers Product Overview



CR SRB SRJ LR TR WR YR RR PR

Series Name	Panel Cut-Out Approx Inches (mm)	Max. UL Current Rating	Boot Splashproof	Approvals				Lighted	Circuitry				Switch Function					Terminals						Actuator		
				UL	CSA	cULus	VDE		SPST	SPDT	DPST	DPDT	On-Off	On-On	(On)-Off	(On)-On	On-Off-On	0.187"QC	0.250"QC	PCB Straight	PCB Left Angle	PCB Right Angle	Solder	Wire Leads	Flat	Curved
CR	1.12 (28.45) x 3 3 widths	16 A 250 V AC 20 A 125 V AC		•	•		•	•	•	•			•	•			•			•			•	•		
SRB	0.760 x 0.508 (19.3 x 12.9)	10 A 250 V AC 10 A 125 V AC	•			•	•		•	•			•	•			•	•	•	•	•		•			
SRJ	ø 0.827 (21.00)	12 A 250 AC 20 A 125 V AC	•			•	•		•	•			•	•			•	•	•	•	•		•			
LR	0.760 x 0.508 (19.3 x 12.9)	10 A 250 V AC 10 A 125 V AC	•	•	•		•	•	•		•						•	•	•	•			•			
TR	1.20 x 0.4333 (30.4 x 11.0)	16 A 250 V AC 16 A 125 V AC	•		•	•	•	•	•	•			•	•	•	•		•					•			
WR	1.19 x 0.867 (30.2 x 22.0)	16 A 250 V AC 16 A 125 V AC	•			•	•	•	•	•	•	•	•	•	•	•		•	•				•	•		
YR	1.19 x 0.867 (30.2 x 22.0)	16 A 250 V AC 20 A 125 V AC	•			•	•	•	•	•	•	•	•	•	•	•		•	•				•	•		
RR	ø 0.787 (20.0)	10 A 250 V AC 10 A 125 V AC	•	•	•		•	•	•	•		•	•				•		•			•				
PR	0.539 x 0.562 (13.7 x 9.2)	3 A 250 V AC 6 A 125 V AC				•	•		•				•							•		•				

Specifications are subject to change without notice.
Please look for additional technical information on the website.
Version 2.0 – November 2025.

ZF Friedrichshafen AG · Graf-Zeppelin-Straße 1 · 91275 Auerbach
switches-sensors@zf.com · <https://switches-sensors.zf.com>

