

Sensors Product Overview



Series Name	Technology				Mounting				Sensor Function										Max. Operating Temp °C	Connection				Magnets Compatible Accessories
	Hall Effect	Reed	Unipolar Switch	Latching	Threaded	Snap In	Mounting Holes	Flange Mount	Magnetic proximity	Speed	Dual Speed	Speed & Direction	Vane	Angular Rotation	Linear	Position	Integral Connector	Pins		Wires				
MP1013	•		•	•		•			•										150		•			
MP1014	•		•	•			•		•										85		•			
MP1007	•		•		•				•										150		•			
MP1021	•		•	•			•		•										85		•			
MP2007		•			•				•										105		•	AS101001		
MP2017		•							•										105		•	AS201701		
MP2018		•					•		•										105		•	AS201801		
MP2019		•					•		•										105		•	AS201901		
VN1015	•						•						•						85		•			
GS1001	•				•					•									125	•	•			
GS1002	•				•					•									125	•	•			
GS1005	•				•					•									125	•	•			
GS1007	•				•					•									125		•			
GS1012	•							•		•									125	•	•			
GS101205	•						•			•									140	•	•			
GS102301	•				•					•									140	•				
GS82	•							•		•									85	•	•			
LIN	•						•									•			140		•			
SD101201	•							•				•							125	•				
SD501201	•							•			•								125	•				
SD74	•							•				•							140		•			
AN1	•						•							•					125	•				
AN8	•						•							•					125	•	•	AS500106 / 709-21955		
AN9	•						•							•					125		•	AS500106 / 709-21955		
ANG	•						•							•					140		•	AS500106 / 709-21955		

Specifications are subject to change without notice.
Please look for additional technical information on the website.
Version 2.0 – November 2025.

ZF Friedrichshafen AG · Graf-Zeppelin-Straße 1 · 91275 Auerbach
switches-sensors@zf.com · <https://switches-sensors.zf.com>

