

Switch Product Overview



Series Name	Size in mm	Switch Type	max. Electrical Rating	UL Approved	ENEC Approved	Mounting				Degree of Protection	Max. Operating Temp °C	Circuitry				Terminals				Actuator Types				Contact System				
						Threaded	Holes	Snap In	Posts (optional)			SPDT	DPDT	SPST	Contact gap > 3 mm	Quick Connect	PCB	Solder	Screw	Wire Leads	Button	Flat Lever	Simulated Roller	Roller	Wiping / Sliding	Positive Break Action	Snap Action	Push Button
DH	8.4 x 2.7 x 6.55	Ultraminiature	500 mA, 30 VDC				•			IP40	85	•				•	•				•					•		
WG	8.3 x 6.5 x 5.3	Subsubminiature	100 mA, 12 VDC						•	IP67	85			•		•	•				•	•	•		•			
DG	12.8 x 5.8 x 6.6	Subsubminiature	3 A, 250 VAC 3 A, 30 VDC		•		•		•	IP40	125	•				•					•	•		•			•	
DJ	15.2 x 8.15 x 6.4	Subsubminiature	2 A, 12 VDC						•	IP67	85	•		•		•	•		•		•					•		
SJ	15.2 x 6.4 x 8.1	Subsubminiature	100 mA, 12 VDC						•	IP67	85			•		•	•		•		•				•			
DK	14.7 x 6.8 x 5.4	Subsubminiature	2 A, 12 VDC						•	IP65*	85	•		•		•	•		•		•	•	•			•		
SK	14.7 x 5.4 x 6.8	Subsubminiature	100 mA, 12 VDC						•	IP65*	85			•		•	•		•		•	•	•		•			
DR	13.7 x 6.8 x 5.4	Subsubminiature	2 A, 12 VDC						•	IP40	85	•				•	•				•					•		
DB	20.0 x 9.65 x 6.5	Subminiature	100 mA / 10 A, 250 VAC	•	•		•		•	IP50	120	•		•		•	•	•			•	•	•	•			•	
DC	20.0 x 10.05 x 6.5	Subminiature	100 mA / 10 A, 250 VAC	•	•		•		•	IP67	120	•		•		•	•	•		•	•	•	•			•		
DZ	20.0 x 9.7 x 6.5	Subminiature	3 A, 250 VAC	•	•		•			IP40	85			•		•					•				•			
DCJK	20.0 x 10.2 x 6.4	Subminiature	100 mA / 10 A, 250 VAC				•		•	IP67	120	•		•		•	•		•		•	•	•	•			•	
D4	27.8 x 15.9 x 10.3	Miniature	100 mA / 21 A 250 VAC	•	•		•			IP40	150	•		•		•	•	•			•	•	•	•			•	
W4	27.8 x 15.9 x 10.3	Miniature	100 mA / 16 A 250 VAC	•	•		•			IP40	85	•		•		•					•	•	•	•	•		•	
E	46 x 28,6 x 16,4	General Purpose	25 A, 250 VAC	•		•	•			IP40	150	•	•	•		•					•	•		•			•	
GP	49.6 x 17.6 x 23.7	General Purpose	25 A, 250 VAC	•	•	•	•			IP40	40	•						•	•		•	•				•		
E/F6	25.6 x 26.6 x 13.72	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•		•					•						•	
E/F7	31.5 x 26.6 x 13.72	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•		•					•						•	
F8	31.5 x 37.5 x 13.3	Panel Mount	100 mA / 16 A, 250 VAC	•	•			•		IP40	85	•	•	•	•	•					•				•		•	

Specifications are subject to change without notice.

*IP67 available on request.

Please look for additional technical information on the website.

Version 3.0 – July 2025.

ZF Friedrichshafen AG · Graf-Zeppelin-Straße 1 · 91275 Auerbach

switches-sensors@zf.com · <https://switches-sensors.zf.com>

