

Sealed Rockers Product Overview



Series Name	Panel Cut-Out Approx Inches (mm)	Max. Current Rating	V DC Max UL Current Rating	Style		Approvals				Circuitry			Switch Function						Terminals			Actuator								
				Rocker	Pushbutton	UL	CSA	UL cUL us	ENEC	Rating	Lighted - neon	Lighted - LED	SPST	SPDT	DPST	DPDT	On-Off	On-On	(On)-Off	On-(Off)	On-(On)	On-Off-On	On-Off-(On)	(On)-Off-(On)	0.187"QC	0.250"QC	PCB Straight	Solder	Screw	Flat
KC	ø 0.795 (20.2)	10(4) A 250 V AC 16 A 125 V AC	•	•			•	•	IP65	•	•			•									•					•		
KD	ø 0.795 (20.2)	10 A 250 V AC 16 A 125 V AC		•			•		IP65	•	•			•	•					•			•					•		
KF	ø 0.795 (20.2)	6 A 250 V AC 10 A 125 V AC			•		•		IP65	•	•			•		•							•					•		
KG	1.441 x 0.835 (36.0 x 21.2)	10 A 250 V AC 20 A 125 V AC		•			•		IP56			•	•	•	•	•	•	•	•	•	•		•		•	•		•		
KM	1.441 x 0.835 (36.0 x 21.2)	10 A 250 V AC 20 A 125 V AC	•	•					IP56		•	•	•	•	•	•	•	•	•	•	•		•				•		•	
KR	0.764 x 0.512 (19.4 x 13.0)	10 A 250 V AC 16 A 125 V AC	•	•			•		IP65	•	•			•	•		•						•				•			
KS	1.441 x 0.835 (36.0 x 21.2)	10 A 277 V AC 16 A 125 V AC		•			•		IP56			•			•								•		•	•		•		
KT	1.454 x 0.602 (36.8 x 15.2)	10(4) A 250 V AC 20 A 125 V AC		•			•	•	IP56		•		•	•									•				•			

**Please look for additional technical information on the website
Version 1.0 - April 2023

